Wall Switches & Remote Controls

	Controls	Brand ^Þ	Wall or Remote	IPI or SP†	On/Off	Battery Strength Indicator	Automatic Battery Backup	Fan Speed	Flame Control	Flame Modulation	Pilot Activation	AUX Function	Temp Readout	Thermostat Mode	Timer Mode	7-Day Programmable
IntelliFire Plus Wireless Controls	IntelliFire Plus RC300	HTL, HNG, QDF	Remote	IPI	•	•	•	•	5 STEP	•	•	(three)‡	•	•	•	
	IntelliFire Plus RC200	HTL, HNG, QDF	Remote	IPI		•	•	•	5 STEP		•					
	IntelliFire Plus RC100	HTL, HNG, QDF	Wall	IPI	•	•	•									
Wireless Controls	TotalRemote RCT-MLT	HTL, HNG, QDF	Remote	Both	•			•	HIGH/LOW				•	•	•	
	SmartRemote-Battery SMART-BATT, 841-970	HTL, HNG, QDF	Remote	Both	•								•	•	•	
	SmartRemote-Hardwired SMART-STATT, 841-0960	HTL, HNG, QDF	Remote	Both	•								•	•	•	
Wired Wall Controls	TotalSwitch WSK-MLT	HTL, HNG, QDF	Wall	Both	•			•	HIGH/LOW		•	(one)	•	•		
	IntelliSwitch®200 WSK200	HTL, HNG, QDF	Wall	IPI	•	•	•	•			•					
	EasySwitch WSK-21 & WSK-21-W	HTL HNG	Wall	Both	•											
	Programmable Thermostat 811-0520	QDF	Wall	Both									•	•		•
	Thermostat 812-3760	QDF	Wall	Both									•	•		

Feature Glossary

On/Off: Turns the flames on and off.

Battery Strength Indicator: IntelliSwitch200 – red led blinks to alert homeowner that new batteries are needed; solid- on indicator signifies that the hearth system is operating on battery power. IntelliFire Plus RC100 & 200 – red led blinks when button is pressed. Lack of red led light signifies that the batteries need changed. IntelliFire Plus RC300 - Displays a battery strength icon.

Automatic Battery Backup: Senses power failure and automatically switches the unit to battery operation, keeping you and your family warm.

Fan Speed: Adjusts the speed of the fan, pushing heat into the room.

Flame: Adjusts the height of the flames, affecting ambiance and heat output.

Pilot Activation: Changes the pilot from 'as-needed' (activated only when the fireplace is turned on) to 'constant-on' (seasonal pilot remains on to improve performance during the coldest times of the year).

AUX Function: Controls assigned auxiliary functions, such as accent lighting or electric embers.

Temp Readout: Communicates room temperature.

Thermostat Mode: Maintains the specified room temperature by adjusting the hearth system, much like a furnace thermostat.

Timer Mode: Shuts flames off automatically at a pre-set time.

7-Day Programmable: Control room temperature settings on a weekly cycle.



The IntelliFire™ Plus Ignition System (IPI Plus) is an advanced intermittent pilot ignition system

a programmable wireless control. IPI Plus constantly monitors ignition, ensures safe functioning and conserves up to \$10/montl in energy costs.

To learn more about IntelliFire Technology, scan the code to the right with your smartphone, or visit fireplaces.com.

† IPI = Intermittent Pilot Ignition
SP = Standing Pilot

‡ Fan speed is one of three auxilliary functions

HTL = Heatilator
HNG = Heat & Glo
QDF = Quadra-Fire



Lakeville, MN (888) 427-3973 (952) 985-6000 Web: fireplaces.com HHT-1003U-0713



Controls

FOR GAS FIREPLACES

meatilator

HEATEGLO

QUADRA-FIRE

Heat at your fingertips - The warmth of home at your control.



Hearth & Home controls are uniquely designed to conveniently start your fire with a simple, easy click. Select the control that best meets your needs and your hearth features.

A sleek wall switch stays in one convenient location while a remote control goes where you go. Wireless controls bring added convenience of handy remote access, as well as a wall docking station.

All controls are UL listed and approved for use with Heatilator, Heat & Glo or Quadra-Fire products.

US LISTED

INTELLIFIRE[™] PLUS WIRELESS CONTROLS

IntelliFire Plus RC300 is specifically designed for use with our new IntelliFire Plus ignition system. It is easyto-use, stylish and ergonomic in design. Features an LCD screen, intuitive menus and large buttons. This wireless control allows flexibility for wall placement, or use as a remote only.

Models: RC300

Features: On/Off, Auto Battery Backup, Pilot Activation, 5 Step Flame Height, Fan Speed (auxiliary 1), two additional Auxiliary Functions, Room Temperature Readout, Thermostat Mode, Timer, Child Lock, Wall **Docking Station**

IntelliFire Plus RC200 is specifically designed for use with our new IntelliFire Plus ignition system. It is easyto-use, stylish and ergonomic in design. As a wireless control, it has the flexibility for wall placement, or use as a remote only.

Models: RC200

Features: On/Off, Auto Battery Backup, Pilot Activation, 5 Step Flame Height, Fan Speed, Child Lock, Wall Docking Station

IntelliFire Plus RC100 Designed specially for fireplaces with IntelliFire Plus, our state-of-the-art intermittent pilot ignition system.

Models: RC100

Features: On/Off

WIRELESS CONTROLS

TotalRemote This remote control effortlessly manages heat output and comfort level. For use with Heatilator, Heat & Glo and Quadra-Fire.

Models: RCT-MLT. 841-0980

Features: Hardwired Receiver. On/Off . Timer Mode. Thermostat Mode, Room Temperature Readout, Flame High/Low, Fan Speed

.....

SmartRemote For homeowners who want an added level of function and convenience in a remote control for fireplaces, stoves, inserts and gas logs. For use with Heatilator, Heat & Glo and Quadra-Fire.

Models: 841-970, 841-0960, SMART-BATT, SMART-STAT

Features: Battery-Powered or Hardwired Receiver, On/Off , Timer Mode, Thermostat Mode, Room Temperature Readout



WIRED WALL CONTROLS

TotalSwitch Command of both comfort and ambiance from one location. For use with Heatilator. Heat & Glo and Quadra-Fire.

Model: WSK-MLT

Features: On/Off, Thermostat Mode, Room Temperature Readout, Auxiliary Function, Flame High/Low, Pilot Activation, Fan Speed

Programmable Thermostat Control your hearth system based on your weekly schedule. UL listed for use with Quadra-Fire.

Model: 811-0520



IntelliSwitch200 Designed specially for Heatilator, Heat & Glo and Quadra-Fire fireplaces with IntelliFire, our UL listed state-ofthe-art intermittent pilot ignition system.

Models: WSK200

Features: On/Off, Auto Battery Backup, Battery Strength Indicator, Pilot Activation, Fan Speed

Thermostat Simple temperature-based control of your hearth system. UL listed for use with Quadra-Fire.

Model: 812-3760

Features: On/Off, Room Temperature Readout













